

## Taraflex Combisport 85 +

A cradle and Batten substructure, comprising of 40mm leg height recycled rubber crumb cradles, 43mm x43mm treated kiln dried, softwood battens, 20mm x 150mm expansion foam perimeter strips and 2.40m x 0.60m x 22mm spruce plywood.

When used in conjunction with the Gerflor Taraflex Sport M Evolution , a multi sport floor covering consisting of a D-Max multi layer surface with a glass fibre mesh and a cell duel density foam backing, 2mm PVC wear layer and Glass Fibre Grid) provides a Combined Elastic sports floor in accordance with En14904 Type C4.

The installation should be carried out in accordance with BS8203-2001, Sub floor to be smooth, hard, clean and dry prior to laying, where applicable sub floor must incorporate a Damp Proof Membrane.

Line marking should be carried out using Gerflor TLD Aqua solvent free paint.

**Flooring:** Cradle & Batten Undercarriage System

**Manufacturer and Reference:** Gerflor Ltd, Wedgnoock House, Warwick. CV34 5AP.

Tel : 01926 622600 email: [contractuk@gerflor.com](mailto:contractuk@gerflor.com)

**Reference:** Gerflor Taraflex Combisport + Undercarriage System

**BS EN 685:** Class N/A

**Finished Floor Height:** 88mm – 97mm (Inclusive of Sport M Evolution Playing Surface).

Consult with Gerflor Ltd for any further requirements and for installation instructions.