

#### TARAFLEX® MULTI-USE

gerflor.co.uk

Description	Standard	Requirement	Units	Taraflex <sup>®</sup> Multi-Use
Product description				
Surface treatment	-	-	-	Triple-Action Protecsol®
Surface complex	-	-	-	D-Max™
Foam	-	-	-	CXP-HD + ™
Thickness	EN ISO 24346 (EN 428)	-	mm	6.2
Weight	EN ISO 23997 (EN 430)	-	kg/m²	4.2
Length*	EN ISO 24341 (EN 426)	-	lm	26.5 Max
Width	EN ISO 24341 (EN 426)	-	lm	1.5
Sport Properties				
Shock absorption	EN 14808	≥ 25	%	P1
Impact Protection Index (IPI)	AC-P90-205	-	-	52
Vertical deformation	EN 14809	≤ 3.5	mm	≤ 2
Sliding coefficient	EN 13036-4	80 to 110	-	80 to 110
Ball bounce	EN 12235	≥ 90	%	≥ 90
Ball speed	ITF	-	-	-
Technical Characteristics				
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance	EN 1517	≥ 8	N/m	≥ 8
Indentation resistance	EN 1516	≤ 0.5	mm	≤ 0.5
Classification				
Fire	EN 13501-1	-	-	C <sub>fl</sub> -s1
Anti-bacterial activity (E. coli - S. aureus - MRSA) (1)	ISO 22196	-	-	> 99% inhibits growth
CE Marking				
C€	EN 14 904	-	-	Fire Shock Absorption Sliding Coefficient Abrasion Resistance Rolling load Resistance

The proposed specifications fall within the tolerance limits usually accepted in this sector whilst still complying with standards.

### Where Champions Play









@GerflorSportsUK

## **CONTACT US NOW**

UNITED KINGDOM: Gerflor Ltd Tel: + 44 (0) 1625 428 922 E-mail: contractuk@gerflor.com

**IRELAND:** Gerflor Ltd Tel: +353 (0) 42 966 1431 E-mail: gerflorirl@gerflor.com





<sup>(</sup>ii) The implementation of an effective cleaning method is the best defence against infection. \*For different roll lengths please contact us.

# TARAFLEX MULTI-USE

Taraflex® Multi-Use is the ideal solution for sports and multipurpose halls. A true sports floor in the P1 category with the triple action Protecsol® surface treatment. It provides excellent indentation resistance and recovery from tables and chairs.

# DESIGNED FOR MULTI-USE SPACES

Protects the users when they are playing, protects itself when they are not.











