



	PRODUCT CHARACTERISTICS			
	Standard	Requirement	Unit	Results
	PRODUCT DESCRIPTION			
Surface treatment	-	-	-	-
Surface complex	-	-	-	-
Foam	-	-	-	-
Thickness	EN ISO 24346	-	mm	1.65
Weight	EN ISO 23997	-	kg/m ²	1.35
Length	EN ISO 24341	-	lm	45 Max
Width	EN ISO 24341	-	lm	2
	SPORT PROPERTIES			
Shock absorption	EN 14808	≥ 25	%	-
Vertical deformation	EN 14809	≤ 3.5	mm	-
Sliding coefficient	EN 13036-4	80 to 110	-	-
Ball bounce	EN 12235	≥ 90	%	-
	TECHNICAL CHARACTERISTICS			
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	-
Impact resistance	EN 1517	≥ 8	N/m	-
Indentation resistance	EN 1516	≤ 0.5	mm	≤ 0.5
	CLASSIFICATION			
Fire	EN 13501-1	-	-	
Treatment	-	-	-	-
	DECLARATION OF PERFORMANCE			
	DOP-002-1001-A	-	-	Fire
	INSTALLATION METHODS			
	Gerflor's recommendation		Unit	Results
Loose lay installation on the subfloor before "flexible" installation of a sports flooring method on it	-	-	-	RH < 80% (BS8203) or < 4.5% humidity (CCM)